## TURBOTOE Steel Toe Cap



The IMPACTO® TURBOTOE safety overshoe protects the toe area from accidental impact, crushing or stubbing. Recommended for use in any industry, especially construction and heavy work environments that carries a risk of toe damage or has a steel toe cap requirement.

Perfect for visitors, casual or temporary workers, management, clerical and sales people. Fits tightly over existing shoes providing a solid protecting cap. Can be comfortably worn over low-heel, dress and running shoes and most boots. The **TURBOTOE** is an affordable alternative to expensive footwear with built-in steel toe cap.

Made of flexible and stretchy, pliable PVC. 100% waterproof, will not harden, stiffen or crack. Treads under sole help prevent slipping.

## IMPACTO TURBOTOE Certifications:

**Satra M21** issue **4** April **2011** - Personal Protective Equipment (PPE) Directive 89/686/EEC and comply with this Directive through the European Standard: EN ISO 20345:2004 Safety footwear.

Slip Resistance – This overshoe has been tested for slip resistance against, Marking code SRA – Ceramic tile floor with sodium lauryl sulphate. Tested flat CoF > 0.32 and tested at 7 in the heel CoF>0.28.

EN ISO 20345:2004 - SB - Toe protection tested with 200 Joules impact and 15 kN compression force.

Canadian CSA Standard - Z195-09 - Protective Footwear. CLASS 7231 01 - OCCUPATIONAL HEALTH AND SAFETY PRODUCTS. Grade 1 - protective toe

Steel toe ASTM F2413-05 M/A/75/C/75.



Sold per pair.
8 pairs per case.
For sizing use your shoe size.
The toe cap is color coded for sizing. If your footwear is bulky, choose next size up.

	Part No.	Toe Color	USA	UK	Europe
	#TTXS	Grey	M: 4 - 5 W: 6 - 7	M: 4.5 - 5.5	38.5 - 39.5
	#TTS	White	M: 6 -7 W: 8 - 9	M: 6 - 7.5	40 - 41.5
	#TTM	Yellow	M: 8 - 9 W: 10 - 11	M: 8 - 9.5	42 - 43.5
	#TTL	Red	M: 10 - 11 W: 12 - 13	M: 10 - 11.5	44 - 45.5
	#TTXL	Blue	M: 12 - 13	M: 12 - 13	46 - 47.5
	#TTXXL	Green	M: 13 - 14	M: 13 - 14	48 - 49.5
ĺ	#TTXXXL	Black	M: 15 - 16	M: 15 - 16	50 - 52

Innovative Protection ISO 9001:2008